

## Product Information Bulletin

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

### One Way Left Sign MUTCD R6-2L



Brimar's Part #: X4537  
MUTCD Compliant

DATE: \_\_\_\_ / \_\_\_\_ / \_\_\_\_

JOB: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_



## Product Information Bulletin

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

### Material Information

MATERIAL THICKNESS	MATERIAL NAME	CHEMICAL RESISTANCE	OUTDOOR DURABILITY	TEMP RANGE	CORNER RADIUS	MOUNT HOLES
.080"	Aluminum Coated Baked Enamel	Fading & Mild Chemicals	5 to 7 Years	-40° to 212° F -40° to 100° C	1-1/2"	2 @ 3/8"

- Aluminum offers longer life expectancy and better resistance to harsh weather conditions.
- Aluminum will not chip, crack or rust.
- **Overlaminated Options (Additional Charge):** 3M Anti Graffiti Over Laminate
- **Mounting:** Post mounting.

.080"	Type I Engineering Grade Reflective on Rust Free Aluminum	Fading & Mild Chemicals	Up to 5 Years (Except Orange Up to 3 years)	-10°F - 130°F	1-1/2"	2 @ 13/8"
-------	---	-------------------------	--	---------------	--------	-----------

- Engineering Grade (Advanced Flexible Engineering Grade 7310) Reflective Sheeting meets ASTM D4956 Type I retro-reflective sheeting standards.
- Graphics are printed using any of the following printing methods: translucent inks (screen printing), applied vinyl graphics and/or thermal transfer (digital printing); translucent ink or film is not applicable to the color black
- **Overlaminated Options (Additional Charge):** 3M Anti Graffiti Over Laminate
- **Mounting:** Post mounting.

.080"	Type IV High Intensity Prismatic Reflective on Rust Free Aluminum	Fading & Mild Chemicals	Up to 7 Years (Except Orange Up to 3 years)	-10°F - 130°F	1-1/2"	2 @ 13/8"
-------	---	-------------------------	--	---------------	--------	-----------

- Any sign laminated with this retro-reflective High Intensity Prismatic (Type IV) Reflective material is 3 to 4 times brighter than any Engineering Grade (EG) sign and can last up to 10 years outdoors.
- High Intensity Prismatic is the replacement material required by many State DOTs when posting new traffic signs. Our High Intensity Prismatic materials provide long-term reflectivity and durability.
- High Intensity Prismatic (HIP) Reflective Sheeting meets ASTM D4956 Type IV retro-reflective sheeting standards.
- Graphics are printed using any of the following printing methods: translucent inks (screen printing), applied vinyl graphics and/or thermal transfer (digital printing); translucent ink or film is not applicable to the color black
- **Overlaminated Options (Additional Charge):** 3M Anti Graffiti Over Laminate
- **Mounting:** Post mounting.

.080"	Type IX White Diamond Grade Reflective on Rust Free Aluminum	Fading & Mild Chemicals	10+ Years	-10°F - 130°F	1-1/2"	2 @ 13/8"
-------	--	-------------------------	-----------	---------------	--------	-----------

- Diamond Grade Type IX Reflective Sheeting is a super-high efficiency, retro-reflective sheeting designed for signs that need to be highly visible during daytime, nighttime, twilight, and inclement weather.
- Excellent visibility at wide entrance and observation angles.
- This sheeting is designed to have the highest retro reflective characteristics at medium and short road distance.
- Diamond Grade fluorescent reflective sheeting provides higher visibility than ordinary (non-fluorescent) colored sheetings.
- Diamond Grade is 10 times brighter than Engineering Grade or High Intensity Prismatic retro-reflective Sheeting.
- **Warranty:** Diamond Grade Reflective Sheeting will remain effective for its intended use and meet minimum required values for coefficient of retro-reflectivity for up to 10 years.

DATE: \_\_\_\_ / \_\_\_\_ / \_\_\_\_

JOB: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_